The LaTeX2HTML Translator

Nikos Drakos,
Computer Based Learning Unit,
University of Leeds.

March 30, 1997

This document accompanies LaTeX2HTML Version 96.1[1]

Abstract

LaTeX2HTML is a conversion tool that allows documents written in LaTeX to become part of the WorldWide Web. In addition, it offers an easy migration path towards authoring complex hypermedia documents using familiar word-processing concepts.

LaTeX2HTML replicates the basic structure of a LaTeX document as a set of interconnected HTML files which can be explored using automatically generated navigation panels. The cross-references, citations, footnotes, the table of contents and the lists of figures and tables, are also translated into hypertext links. Formatting information which has equivalent "tags" in HTML (lists, quotes, paragraph breaks, type styles, etc.) is also converted appropriately. The remaining heavily formatted items such as mathematical equations, pictures or tables are converted to images which are placed automatically at the correct positions in the final HTML document.

LaTeX2HTML extends LaTeX by supporting arbitrary hypertext links and symbolic cross-references between evolving remote documents. It also allows the specification of *conditional text* and the inclusion of raw HTML commands. These hypermedia extensions to LaTeX are available as new commands and environments from within a LaTeX document.

This document presents the main features of LaTeX2HTML, and describes how to obtain, install, and use it.

[1] This manuscript was updated to version 96.1 as indicated by the changebars by Herbert W. Swan <dprhws@edp.Arco.com> and converted to LaTeX 2_ε by Michel Goossens <goossens@cern.ch>.

Contents

[2] This feature is supported only for users of LaTeX 2_ε.

List of Figures

List of Tables

[3] http://csep1.phy.ornl.gov/csep.html

1 Overview

This document describes the LaTeX2HTML translator which:

- breaks up a document into one or more components as specified by the user[4],
- provides optional, customizable iconic navigation panels on every page which contain links to other parts of the document, or other documents,
- hadles inlined equations ($\sum_{i=1}^{n} x_i = \int_0^1 f$), handles equation alignment ($A_{B_{C+D}}$), right-justified numbered equations (see equation 2), tables (see Table 2), or figures (see Figure 2), and *any arbitrary environment*[5],
- figures or tables can be arbitrarily scaled and oriented and shown either as inlined images or "thumbnail" sketches
- can produce output suitable for browsers that support inlined images or character based browsers (as specified by the user),
- handles definitions of new commands, environments, and theorems even when these are defined in external style files[6],
- handles footnotes[7], tables of contents, lists of figures and tables, bibliographies, and can generate an index,
- translates cross-references into hyperlinks and extends the LaTeX cross-referencing mechanism to work not just within a document but *between documents* which may reside in remote locations,
- translates LaTeX accent and special character commands (e.g. Ȧ Øö £©¶) to the equivalent ISO-LATIN-1 or Unicode character set where possible,
- recognizes hypertext links (to multimedia resources or arbitrary internet services such as sound/video/ftp/http/news) and links which invoke arbitrary program scripts, all expressed as LaTeX commands,
- recognizes *conditional text* which is intended only for the hypertext version, or only for the paper (DVI) version,
- can include raw HTML in a LaTeX document (e.g. in order to specify interactive forms),
- can deal sensibly at least with the *Common LaTeX commands* summarized at the back of the LaTeX blue book [1],

[4] The user can specify the *depth* at which the document should not be broken up any further.

[5] These are passed to LaTeX and then converted to images which are either included in the document or are made available through hypertext links.

[6] This allows the definition of HTML macros in LaTeX !

[7] Like this!

- will try and translate any document with embedded LaTeX commands irrespective of whether it is complete or syntactically legal.
- can be configured to translate equations and/or tables either as GIF images or as HTML 2.1 or 3.0 markup, as browsers become available which are suitable for the task.
- links symbolic references across document segments which are independently processed.

A selection of documents illustrating the different contexts in which LaTeX2`HTML` has been used is available at
http://www-dsed.llnl.gov/files/programs/unix/latex2html/manual/.

2 User Manual

To use LaTeX2`HTML` simply type `latex2html <file>.tex`. The `.tex` suffix is optional and will be supplied by the program if it is omitted by the user. This will create a new directory called `file` which will contain the generated HTML files, some log files and possibly some images. To view the result use an HTML viewer such as NCSA Mosaic or Netscape Navigator on the main HTML file which is `file/file.html`. This file will contain navigation links to the other parts of the generated document.

It is possible to customize the output from LaTeX2`HTML` using a number of command line options (see Section 2.1) with which you can specify how to break up the document, where to put the generated files, what the title is, what the signature at the end of each page is, what to put in the navigation panel, what kind of extra information to include about the document, whether to retain the original LaTeX section numbering scheme, etc.

Also, the LaTeX2`HTML` script includes a short manual which can be viewed by saying `%nroff -man latex2html`.

2.1 Command Line Options

The command line options described below can be used to change the default behavior of LaTeX2`HTML`. Alternatively, the corresponding environment variables in the initialization file `.latex2html-init` may be changed, in order to achieve the same result.

-split *num* Stop splitting sections into separate files at this depth. A value of 0 will put the document into a single HTML file. The default is 8.

-link *num* Stop revealing child nodes at each node at this depth. (A node is a part/chapter/section/subsection/subsubsection etc.). A value of 0 will show no links to child nodes, a value of 1 will show only the immediate descendents, etc. A value at least as big as that of the `-split` option will produce a table of contents for the tree structure, rooted at each given node. The default is 4.

-nolatex Disable the mechanism for passing unknown environments to LaTeX for processing. This can be thought of as "draft mode" which allows faster translation of the basic document structure and text, without fancy figures, equations or tables.

This option has been superceded by the `-no_images` option (see below).

-external_images Instead of including any generated images inside the document, leave them outside the document and provide hypertext links to them.

-ascii_mode Use only ascii characters and do not include any images in the final output. In ascii mode the output of the translator can be used on character based browsers which do not support inlined images (the `<IMG>` tag).

-t *top-page-title* Name the document using this title.

-up_url *URL* Specifies a universal resource locator (URL) to associate with the UP button of the top-level navigation panel.

-up_title *string* Specifies a title associated with this URL.

-down_url *URL* Specifies a URL for the NEXT button of the bottom-level navigation panel.

-down_title *string* Specifies a title associated with this URL.

-contents *URL* Specifies a URL for the table of contents button for document segments that would not otherwise have one.

-index *URL* Specifies a URL for the index button for document segments that otherwise would not have an index.

-external_file *filename-prefix* Specifies the prefix of the `.aux` file that this document segment should read. The `.aux` extension will be appended to this prefix. This file is necessary for document segments to obtain figure and section numbers from LaTeX.

-dir *output-directory* Redirect the output to this directory.

-no_subdir Place the generated HTML files in the current directory. The default behaviour is to create (or reuse) another file directory.

-prefix *filename-prefix* The `filename-prefix` will be prepended to all `.gif, .pl` and `.html` files produced, except for the top-level `.html` file. This will enable multiple products of LaTeX2`HTML` to peacefully coexist in the same directory. Do **not**, however, attempt to *simultaneously* run multiple instances of LaTeX2`HTML` using the same output directory, or various temporary files will overwrite each other.

-font_size *size* This option provides better control over the font size of environments processed by LaTeX. *size* must be one of the font sizes that LaTeX recognized; i.e. `10pt, 11pt, 12pt`, etc. The default size is the same as the LaTeX document. Whatever size is selected, it will be magnified by the installation variables, $MATH_SCALE_FACTOR or $FIGURE_SCALE_FACTOR.

-no_tex_defs If specified, the translator will make no attempt to interpret raw TeX commands. This feature will enable sophisticated authors the ability to insert arbitrary TeX commands in environments that are distined to be processed by LaTeX anyway (e.g. figures, theorems, etc.)

-ps_images Use links to external postscript images rather than inlined GIF images.

-address ***author-address*** Sign each page with this address.

-no_navigation Disable the mechanism for putting navigation links in each page.

-top_navigation Put navigation links at the top of each page.

-bottom_navigation Put navigation links at the bottom of each page AS WELL as the top.

-auto_navigation Put navigation links at the top of each page. If the page exceeds `$WORDS_IN_PAGE` number of words (the default is 450) then put one at the bottom of the page as well.

-index_in_navigation Put a link to the index page in the navigation panel if there is an index.

-contents_in_navigation Put a link to the table of contents in the navigation panel if there is a table of contents.

-next_page_in_navigation Put a link to the next logical page in the navigation panel.

-previous_page_in_navigation Put a link to the previous logical page in the navigation panel.

-info ***string*** Generate a new section *About this document ...* containing information about the document being translated. The default is to generate such a section with information on the original document, the date, the user and the translator. An empty string (or the value 0) disables the creation of this extra section. If a non-empty string is given, it will be placed in the contents of the *About this document ...* section instead of the default information.

-reuse ***reuse_option*** The *reuse_option* specifies how or whether image files are to be shared or recycled, and accepts three valid options:

- **0** Do not ever share or recycle image files. This choice also invokes an interactive session prompting the user about what to do about a pre-existing `HTML` directory, if it exists.
- **1** Recycle image files from a previous run if they are available, but do not share identical images that must be created in this run.
- **2** Recycle image files from a previous run and share identical images from this run. (This is the default).

Section 4.5 provides additional information about image reuse.

-no_reuse Do **not** share or recycle images generated during previous translations. This is equivalent to **-reuse 0**. (This will enable the initial interactive session during which the user is asked whether to reuse the old directory, delete its contents or quit)

-init_file file Load the specified file. This Perl file will be loaded after loading $HOME/.latex2html-init (if one exists). It can be used to change the default options.

-no_images Do not attempt to produce any inlined images. The missing images can be generated "off-line" by restarting LaTeX2HTML with the option `-images_only`.

-images_only Try and convert any inlined images that were left over from previous runs of LaTeX2HTML.

-show_section_numbers Show section numbers. By default the section numbers are not shown in order to encourage the use of particular sections as standalone documents. In order to be shown, section titles must be unique and must not contain inlined graphics.

-html_version *version* This specifies the `HTML` version to generate. Currently, versions 2.1, 2.2, 3.0 and 3.1 are available. The default version is 2.0.

-vs Print the current version of LaTeX2HTML.

-h Print out the list of options.

2.2 Extending the Translator

As the translator covers only partially the set of LaTeX commands and because new LaTeX commands can be defined arbitrarily using low level TeX commands, the translator should be flexible enough to allow end users to specify how they want particular commands to be translated.

2.2.1 Adding Support for Specific Style Files

LaTeX2HTML provides a mechanism where code to translate specific style files is automatically loaded if such code is available. When the use of a style file such as `german.sty` is detected in a LaTeX source document, the translator looks for a file `LATEX2HTMLDIR/styles/german.perl`. If one is found, then it will be loaded into the main script.

This mechanism will help to keep the core script smaller as well as make it easier for others to contribute and share solutions on how to translate specific style files. The current distribution includes the files listed in Table 1. These will provide good examples of how you can create your own extensions to LaTeX2HTML. The problem however, is that writing such extensions requires an understanding of Perl and of the way LaTeX2HTML is organized. More user-friendly interfaces will be investigated.

At the moment a rudimentary mechanism is provided so that a user can ask for particular commands and their arguments either to be ignored or passed on to LaTeX for processing (the default behavior for unrecognized commands is for their arguments to remain in the HTML text). Commands that are passed on to LaTeX are converted to images which are either "inlined" in the main document or become accessible via hypertext links. Simple extensions using the commands above may be included in the `LATEX2HTMLDIR/latextohtml.config` file or in each personal `HOME/.latex2html-init` initialization file.

`.perl` file	Description
`alltt`	Supports the LaTeX 2_ε's `alltt` package
`changebar`	Provides rudimentary change bar support
`color`	Causes colored text to be processed as ordinary text by LaTeX2HTML
`french`	Special support for the French language
`epsfig`	Processes embedded figures not enclosed in a `figure` environment
`floatfig`	Processes floating figures
`german`	Special support for the German language
`graphics`	Supports commands in the `graphics` package
`graphicx`	Supports the alternate syntax of graphics commands
`heqn`	Alters the way displayed equations are processed
`htmllist`	Provides support for fancy lists
`makeidx`	Generates indices
`texdefs`	Supports raw TeX commands
`wrapfig`	Supports wrapped figures

Table 1: Supported LaTeX2HTML style files

2.2.2 Asking the Translator to Ignore Commands

Commands that should be ignored may be specified in the `.latex2html-init` file as input to the `ignore_commands` subroutine. Each command which is to be ignored should be on a separate line followed by compulsory or optional argument markers separated by `#`'s e.g.[8]:

```
<cmd_name>#{}# []# {}# [] ...
```

`{}`'s mark compulsory arguments and `[]`'s optional ones.

Some commands may have arguments which should be left as text even though the command should be ignored (e.g. `mbox`, `center`, etc.). In these cases the arguments should be left unspecified.

Here is an example of how this mechanism may be used:

```
&ignore_commands( <<_IGNORED_CMDS_);
documentstyle # [] # {}
linebreak# []
center
<add your commands here>
_IGNORED_CMDS_
```

[8] It is possible to add arbitrary Perl code between any of the argument markers which will be executed when the command is processed. For this however a basic understanding of how the translator works and of course Perl is required.

2.2.3 Asking the Translator to Pass Commands to LaTeX

Commands that should be passed on to LaTeX for processing because there is no direct translation to HTML may be specified in the `.latex2html-init` file as input to the `process_commands_in_tex` subroutine. The format is the same as that for specifying commands to be ignored. Here is an example:

```
&process_commands_in_tex (<<_RAW_ARG_CMDS_);
fbox # {}
framebox # [] # [] # {}
<add your commands here>
_RAW_ARG_CMDS_
```

3 Hypertext Extensions to LaTeX

This section describes how you can define hypertext entries in your `HTML` documents from within your LaTeX source. These are implemented as new LaTeX commands which have special meaning during the translation to `HTML` but are mostly ignored when processed by LaTeX.

All the new commands used in the sections below are defined in the file `html.sty` which is part of the distribution. *This file must be included in any LaTeX document using these features* by one of the following methods:

- Including `html` as an optional argument to the LaTeX `documentstyle` command;
- Including `html` in the LaTeX 2_ε `usepackage` command; or
- Pasting the definitions of individual commands directly into the text!

3.1 Hyperlinks in LaTeX

Arbitrary hypertext references are available through the commands `htmladdnormallink` and `htmladdimg`.

These are defined as follows:

```
\htmladdnormallink{<text>}{<URL>}
\htmladdimg{<URL>}
```

The first command expects some text as the first argument and a URL as the second argument. When processed by LaTeX (i.e. in the `dvi` or `ps` output files), the URL will have no effect. But when processed by the translator, the URL will be used to provide an active hypertext link (to another file, picture, sound file, movie, etc) e.g.

```
\htmladdnormallink{<URL>}
{http://www.ncsa.uiuc.edu/demoweb/url-primer.html}
```

A similar command called `htmladdnormallinkfoot` takes the same two arguments and has the same effect when generating HTML as `htmladdnormallink`. But when processed by LaTeX it shows the URL as a footnote.

In a similar way, the argument of the `htmladdimg` command should be a URL pointing to an image. This URL is ignored in the LaTeX hard copy output.

3.2 Including Arbitrary HTML Markup

Raw HTML or HTML+ tags and text may be included using the environment `rawhtml`. This can be used to take advantage of new HTML+ facilities as soon as they become available. A particularly good use of this feature is in the creation of interactive electronic forms from within a LaTeX document. When producing the paper (DVI) version of a document the `rawhtml` environment is ignored.

Here is an example:

```
\begin{rawhtml}
<HR>
<FORM ACTION="http://cbl.leeds.ac.uk/nikos/doc/error.html">
<OL>
<LI> <INPUT TYPE="checkbox" NAME="wp" VALUE="word"> Word for
Windows.
<LI> <INPUT TYPE="checkbox" NAME="wp" VALUE="wp"> Word Perfect.

<LI> <INPUT TYPE="checkbox" NAME="wp" VALUE="latex"> LaTeX.
<LI> Plain Text Editors (Please Specify): <INPUT TYPE="text" NAME="other_ed">
</OL>
So, what do think (comments please): <BR>
<INPUT TYPE="text" SIZE=45,4 NAME="other_wp">

<INPUT TYPE="submit" VALUE="submit this form but don't expect much!">
</FORM>
<HR>
\end{rawhtml}
```

The result is shown below:

Warning: Avoid using LaTeX commands involving counters (e.g. numbered figures or equations) in conditional text because this may disrupt the values of the counters in the electronic version.

3.3 Conditional Text

Conditional text can be specified using the environments `latexonly` and `htmlonly`. These allow writing parts of a document which are intended only for electronic delivery or only for paper-based delivery.

This would be useful for example in adding a long description of a multimedia resource in the paper version of a document. Such a description would be redundant in the electronic version, as the user can have direct access to this resource.

Here is an example of the use of the `latexonly` environment:



Figure 1: An electronic form. Of course in the online version of this document the form above would be active.

```
\begin{latexonly}
\begin{figure}
    \begin{center}
    \fbox{\includegraphics[width=4in]{eform.ps}}
    \end{center}
    \caption{An electronic form. Of course in the online version of this
     document the form above would be active.}
\end{figure}
\end{latexonly}
```

There are also shorthand notations to accomplish the same thing with less typing. The `\latex{}` command causes everything within the braces to be processed by LaTeX, but ingored by LaTeX2HTML. Conversely, the `\html{}` command causes everything within the braces to be ignored by LaTeX and processed by LaTeX2HTML. Finally the command `\latexhtml{}{}` causes everthing within the first set of braces to be processed exclusively by LaTeX, with the contents of the second set of braces processed solely by LaTeX2HTML.

3.4 Symbolic References Shown as "Hyperized" Text

In printed documents cross-references are shown through a *numerical or symbolic indirection* e.g. "see Figure 1" (numeric indirection), or "see section "Changes" (symbolic indirection). LaTeX2HTML can mirror this mechanism using the same numeric or symbolic references, or when these are not appropriate by using iconic references.

In a hypertext document however, cross-references can be shown without any indirection just by highlighting a relevant piece of text. This can make a document more readable as it removes unnecessary information.

A single new LaTeX command `hyperref` can be used for specifying how a cross-reference should appear both in the printed document and in the hypertext version.

Assuming that the label `sec:cond` is defined somewhere in a document the command `hyperref` which takes 4 arguments can be used in the same document as follows:

```
\emph{Is the concept of
\hyperref
% This will be highlighted in the hypertext version
{conditional text} % argument #1
% This will be shown in the printed version
% followed by a numeric reference ...
{conditional text (see Section }   % argument #2
% ... followed by this text
{ for more information)}  % argument #3
% This the common label
{sec:cond} % argument #4
a good idea? }
```

Here is how it will be shown:
Is the concept of conditional text (see Section 8.6 for more information) a good idea?

In the hypertext version what would appear is:
Is the concept of conditional text a good idea?
Of course conditional text would be an active hypertext link.

Another command also defined in `html.sty` is `htmlref` which has the same effect as `hyperref` during the conversion to HTML. It takes two arguments, some text and a label. In the HTML version the text will be "hyperized" pointing to the label. In the paper version the text will be shown as it is and the label will be ignored eg

```
With \texttt{htmlref} \htmlref{it's easy to make links}{fig:example}.
```

In the HTML version it will be shown as:
With `htmlref` it's easy to make links.

3.5 Symbolic References Between Living Documents

The method of the previous section to generated symbolic hyperized links can easily be extended to *external* documents processed by LaTeX2`HTML`. When LaTeX2`HTML` processes a document, it generates a `perl` file named `labels.pl` which contains a list of all the symbolic labels that were defined, along with their locations. The name of this file is preceeded by the filename prefix to allow different document segments to share the same directory. Links to an external document are then possible once a connection is established to that document's `labels.pl` file. This connection is established by the `\externallabels` command:

```
\externallabels{<URL to directory of external document>}
               {<external document labels.pl file>}
```

The first argument to `externallabels` should be a URL to the directory containing the external document. The second argument should be the full pathname to the `labels.pl` file belonging to the external document. Note that for *remote* external documents it is necessary to copy the `labels.pl` file locally so that it can be read when processing a local document that uses it. The command `externallabels` can be used once for each external document in order to import the *external labels* into the current document. A warning is given if `labels.pl` cannot be found.

If a symbolic reference made in either of the commands described in Section 3.4 is not defined within the document itself, LaTeX2HTML will look for that reference in one of the external files.[9] After any modifications in an external document (sections added/deleted, segmentation into different physical parts, etc.) a new `labels.pl` will be generated. If the `externallabels` command in another document contains the correct address to the `labels.pl` file, then the cross-references will be realigned after running the local document through the translator.

There is also a mechanism analogous to the `label-ref` pairs of LaTeX, which can be used only within a single document. These labels are called *internal labels*, as opposed to the external labels defined above.

Either type of label is defined with a LaTeX `label` command. Labels can be referenced *within* a document using a `ref` command. When processed by LaTeX, each `ref` command is replaced by the section number in which the corresponding `label` occurred. When processed by the translator, each `ref` is replaced by a hypertext link to the place where the corresponding `label` occurred. This mechanism can be extended to external documents by the `\externalref{}` command:

```
\externalref{<symbolic label in remote document>}
```

The argument to `externalref` may be any symbolic label defined in any of the external documents in the same Such references to external symbolic labels are then translated into hyperlinks pointing to the external document.

3.5.1 A Cross-referencing example

To understand this mechanism better consider how you would maintain a link to this section (of the hypertext version of this document) from one of your documents without using labels. Sure enough you can get the name of the physical file that this section is in. This however is very likely to change and any links to it will become invalid. To update your link, the name of the new file must be found and your link changed by hand. Also there is no general updating mechanism so the only way to find out if your document is pointing to the right place is by actually following the link and then doing a manual update[10].

Now consider how it could be done with symbolic labels. First you have to import the labels used in this document by copying the file labels.pl, saving it say in `/tmp/labels.pl`, and then adding anywhere in your document:

[9] Care must be taken to ensure that critical symbolic references are unique across related documents.

[10] Link validation can be done automatically but the updating must be done manually when filenames have changed (assuming no other symbolic label mechanism is available).

```
\externallabels{http://cbl.leeds.ac.uk/nikos/tex2html/doc/manual}
               {/tmp/labels.pl}
```

After that you can use the label `crossrefs` defined at the beginning of this section[11] as follows:

```
\externalref{crossref}
```

This will be translated into the appropriate hyperlink to this page. If there are any changes in this document and you would like to bring your document upto date you have to copy labels.pl again and rerun the translator on your document. Of course if I move the directory containing the HTML files for this document somewhere else then you would have to make a change in the argument of the `externallabels` command to reflect this.

It is obvious that some level of collaboration is required between authors trying to maintain cross-references between different documents. Using symbolic labels makes this a lot easier (especially for documents written by the same author).

3.6 Document Segmentation[12]

One of the greatest appeals of the World Wide Web is its high connectivity through hyperlinks. As we have seen, the LaTeX author can provide these links either manually or symbolically. Manual links are more tedious because a URL must be provided by the author for every link, and updated every time the target documents change. Symbolic links are more convenient, because the translator keeps track of the URLs. Earlier releases of LaTeX2`HTML` required the entire document to be processed together if it was to be linked symbolically. However, it was easy for large documents to overwhelm the memory capacities of moderate sized computers. Furthermore, processing time could become prohibitively high, if even a small change required the entire document to be reprocessed.

For these reasons, program segmentation was developed. This feature enables the author to subdivide his document into multiple *segments*. Each segment can be processed independently by LaTeX2`HTML`. Hypertext links between segments can be made symbolically, with references shared through auxiliary files. If a single segment changes, only that segment needs to be reprocessed (unless a label is changed that another segment requires). Furthermore, the entire document can be processed without modification by LaTeX to obtain the printed version. The top level segment that LaTeX reads is called the *parent* segment. The others are called *child* segments.

Program segmentation does require a little more work on the part of the author, who will now have to untertake some of bookkeeping formerly performed exclusively by LaTeX2`HTML`. The following four LaTeX extensions carry out segmentation:

`\segment{file}{sec-type}{heading}` This commands indicates the start of a new program segment. This segment resides in `file.tex`, represents the start of a new LaTeX sectional unit of type `sec-type` (e.g., `section, chapter,` etc.), and has a heading of `heading`. A variation of this command, `\segment*`, is provided for segments that are not to appear in the table of contents. These commands perform the following operations in LaTeX:

[11] You either have to guess the role of each label by looking at the `labels.pl` file or by asking the author!

[12] This feature is supported only for users of LaTeX 2_ε.

1. The specified sectioning command is executed.
2. LaTeX will write its section and equation counters into an auxiliary file, named `file.ptr`. It will also write an `\htmlhead` command to this file. This information will tell LaTeX2HTML how to initialize itself for the new document segment.
3. LaTeX will then proceed to input and process the file, `file.tex`.

The `\segment` and `\segment*` commands are ignored by LaTeX2HTML.

`\internal[type]{prefix}` This command directs LaTeX2HTML to load intersegment information of type `type` from the file `<prefix><type>.pl`. Each program segment must be associated with a unique filename prefix, specified either through a command line option, or through the installation variable `$AUTO_PREFIX`. The information `type` must be one of the following:

internals This is the default type, which need not be given. It specifies that the internal labels from the designated segment are to be input and made available to the current segment.

contents The table of contents information from designated segment are to be made available to the current segment.

sections Sectioning information is to be read in. Note that the segment containing the table of contents requires both contents and sections information from all other program segments.

figure Lists of figures from other segments are to be read.

table Lists of tables from other segments are to be read.

index Index information from other segments are to be read.

`\startdocument` Only the parent segment contains `\begin{document}` and `\end{document}` statements. The child segments, therefore, cannot be processed separately by LaTeX (without modification). They can be processed separately by LaTeX2HTML, provided it is told where the end of the end the LaTeX preamble is. This is the function of the `\startdocument` directive. It substitutes for `\begin{document}` in child segments, but is otherwise ignored by both LaTeX and LaTeX2HTML.

`\htmlhead{sec-type}{heading}` This command is not normally placed in the document at all. It is automatically passed from parent to child via `file.ptr`. It identifies to LaTeX2HTML that the current segment is a LaTeX sectional unit of type `sec-type`, with the specified heading. This command is ignored by LaTeX itself.

3.6.1 A segmentation example

The best way to illustrate document segmentation is through a simple example. Suppose that a document is to be segmented into one parent and two child segments. Let the parent segment be `report.tex`, and the the two child segments be `sec1.tex`, and `sec2.tex`. The latter are translated with filename prefixes of `s1` and `s2`, respectively. This example is